



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### Product identifier

**Name of product** Chrome Silver Spray (GB)  
Code-Nr. 111030

**Relevant identified uses of the substance or mixture and uses advised against**  
**Recommended intended purpose(s)**  
Technical Aerosols

### Details of the supplier of the safety data sheet

**Manufacturer/distributor** WEICON GmbH & Co. KG  
Königsberger Straße 255, DE-48157 Münster  
Postbox 84 60, DE-48045 Münster  
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244  
E-Mail : info@weicon.de  
Internet : www.weicon.de

**Advice** Abteilung Angebote, Verkauf, Export  
Phone ++49(0)251 / 9322 - 0  
E-mail (competent person):  
info@weicon.de

### Emergency telephone number

**Emergency advice** Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)  
Phone ++49(0)228-19 240

## SECTION 2: Hazards identification

### Classification of the substance or mixture

#### Classification according to 67/548/EEC or 1999/45/EC

F+; R12  
Xi; R36  
R52/53  
R66  
R67

#### R-phrases

12 Extremely flammable.  
36 Irritating to eyes.  
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
66 Repeated exposure may cause skin dryness or cracking.  
67 Vapours may cause drowsiness and dizziness.

### Label elements

#### Labelling according to 67/548/EEC or 1999/45/EC

#### Remarks for labelling

The product is classified and labelled in accordance with EC directives/German regulations on dangerous substances.

**F+** Extremely flammable  
**Xi** Irritant

#### R-phrases

12 Extremely flammable.  
36 Irritating to eyes.  
52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
66 Repeated exposure may cause skin dryness or cracking.



## Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

22.06.2012

revision

01.05.2012 (GB) Version 7.0

**Chrome Silver Spray (GB)**

67 Vapours may cause drowsiness and dizziness.

**S-phrases**

- 23 Do not breathe spray.  
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.  
51 Use only in well-ventilated areas.

**Special rules for supplemental label elements for certain mixtures**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Other hazards****Information pertaining to special dangers for human and environment**

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

**SECTION 3: Composition/ information on ingredients****Mixtures****Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
67-64-1	200-662-2	acetone	10 - 25	F R11; Xi R36; R66; R67
78-93-3	201-159-0	butanone	2,5 - 10	F R11; Xi R36; R66; R67
106-97-8	203-448-7	butane	10 - 25	F+ R12
7429-90-5	231-072-3	aluminium powder (stabilised)	<= 2,5	F R11-15
123-86-4	204-658-1	n-butyl acetate	2,5 - 10	R10; R66; R67
1330-20-7	215-535-7	xylene	2,5 - 10	R10; Xn R20/21; Xi R38
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom. (NOTA P)	2,5 - 10	R10; Xn R65; Xi R37; N R51/53; R66; R67
74-98-6	200-827-9	propane	10 - 25	F+ R12

  

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-64-1	200-662-2	acetone	10 - 25	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
78-93-3	201-159-0	butanone	2,5 - 10	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
106-97-8	203-448-7	butane	10 - 25	Flam. Gas 1, H220 / Press. Gas
7429-90-5	231-072-3	aluminium powder (stabilised)	<= 2,5	Water-react. 2, H261 / Flam. Sol. 1, H228
123-86-4	204-658-1	n-butyl acetate	2,5 - 10	Flam. Liq. 3, H226 / STOT SE 3, H336
1330-20-7	215-535-7	xylene	2,5 - 10	Flam. Liq. 3, H226 / Acute Tox. 4, H332 / Acute Tox. 4, H312 / Skin Irrit. 2, H315
64742-95-6	265-199-0	Solvent naphtha (petroleum), light arom. (NOTA P)	2,5 - 10	Flam. Liq. 3, H226 / Asp. Tox. 1, H304 / STOT SE 3, H335 / Aquatic Chronic 2, H411 / STOT SE 3, H336 / , EUH066
74-98-6	200-827-9	propane	10 - 25	Flam. Gas 1, H220 / Press. Gas

**SECTION 4: First aid measures****Description of first aid measures****General information**

Remove contaminated soaked clothing immediately.

**In case of inhalation**

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.



---

**In case of skin contact**

In case of contact with skin wash off with soap and water.

**In case of eye contact**

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

**In case of ingestion**

Do not induce vomiting.  
Refer to medical treatment.

**Most important symptoms and effects, both acute and delayed**

No information available.

**Indication of any immediate medical attention and special treatment needed**

No information available.

---

**SECTION 5: Firefighting measures**

**Extinguishing media**

**Suitable extinguishing media**

Dry powder  
Carbon dioxide  
sand

**Extinguishing media which must not be used for safety reasons**

water

**Special hazards arising from the substance or mixture**

Danger of bursting  
Fire gas of organic material has to be classed invariably as respiratory poison.

**Advice for firefighters**

**Special protective equipment for fire-fighters**

Use breathing apparatus with independent air supply.  
Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

**Additional information**

Vapours are heavier than air and will spread on the ground.  
Cool endangered containers with water spray jet.  
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**SECTION 6: Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation.  
Use personal protective clothing.  
Keep away sources of ignition.

**Environmental precautions**

Do not discharge into the drains or bodies of water..

**Methods and material for containment and cleaning up**

Take up with absorbent material.  
After taking up the material dispose according to regulation.

**Reference to other sections**

No information available.



## SECTION 7: Handling and storage

### Precautions for safe handling

#### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking  
Do not spray on a naked flame or any incandescent material.  
Pressurized container.  
Do not pierce or burn even after use.  
The product is combustible.  
Vapours can form an explosive mixture with air.  
Avoid effect of heat.

### Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

#### Further information on storage conditions

Protect from heat and direct solar radiation.  
Storage temperature may not exceed 50°C (=122°F).  
Store container at cool and aired place.

#### Specific end use(s)

No information available.

## SECTION 8: Exposure controls/personal protection

### Control parameters

#### Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
67-64-1	Acetone	8 hours	1210	500	EH40/2005
		Short-term	3620	1500	
7429-90-5	Aluminium metal: inhalable dust	8 hours	10		EH40/2005
7429-90-5	Aluminium metal: respirable dust	8 hours	4		EH40/2005
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
78-93-3	Butan -2-one (methyl ethyl ketone)	8 hours	600	200	EH40/2005
		Short-term	899	300	
1330-20-7	Xylene, o-, m-, p- or mixed isomers	8 hours	220	50	EH40/2005
		Short-term	441	100	

#### Indicative occupational exposure limit values (91/322/EEC, 2000/39/EC, 2006/15/EC or 2009/161/EU)

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
1330-20-7	xylene, mixed isomers, pure	8 hours	221	50	skin
		Short-term	442	100	
67-64-1	acetone	8 hours	1210	500	
78-93-3	butanone	8 hours	600	200	
		Short-term	900	300	

### Exposure controls

#### Respiratory protection

If ventilation insufficient, wear respiratory protection.  
Short-term: filter apparatus, filter AX, otherwise environment-independent breathing apparatus.

#### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.  
Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.  
Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: butyl rubber, 0,7mm; 480min

#### Eye protection

safety goggles



**Skin protection**

protective clothing

**General protective measures**

Avoid contact with eyes and skin  
Do not inhale gases/vapours/aerosols.

**Hygiene measures**

At work do not eat, drink, smoke or take drugs.  
Wash hands before breaks and after work.  
Use barrier skin cream.

**Additional advice on system design**

Sufficient ventilation and exhaustion.

**SECTION 9: Physical and chemical properties**

**Information on basic physical and chemical properties**

**Form**

aerosol

**Colour**

silver-grey

**Odour**

solvent-like

**Important health, safety and environmental information**

	Value	Temperature	at	Method	Remark
<b>boiling point</b>	-44 °C				
<b>Flash point</b>	-97 °C				
<b>Ignition temperature</b>	365 °C				
<b>Lower explosion limit</b>	1,5 Vol-%				
<b>Upper explosion limit</b>	13 Vol-%				
<b>Vapour pressure</b>	8300 hPa	20 °C			
<b>Density</b>	not determined				
<b>Solubility in water</b>					immiscible

**Explosive properties**

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

**Other information**

No information available.

**SECTION 10: Stability and reactivity**

**Reactivity**

No information available.

**Chemical stability**

No information available.

**Possibility of hazardous reactions**

No information available.

**Conditions to avoid**

Keep away from heat.  
Formation of explosive gas/air mixtures.

**Incompatible materials**

No information available.

**Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

**Thermal decomposition**

Remark No decomposition if used as directed.

**SECTION 11: Toxicological information****Information on toxicological effects****Acute toxicity/Irritability/Sensitization**

	Value/Validation	Species	Method	Remark
<b>Irritability skin</b>	non-irritant			
<b>Irritability eye</b>	irritant			
<b>Skin sensitization</b>	non-sensitizing			

**Experiences made from practice**

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation. Vapours may cause dizziness, headaches and tiredness

**Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

Labelling in compliance with the assessment procedure specified in the EC guidelines 1999/45/EC.

**SECTION 12: Ecological information****Toxicity**

No information available.

**Persistence and degradability**

No information available.

**Bioaccumulative potential**

No information available.

**Mobility in soil**

No information available.

**Results of PBT and vPvB assessment**

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

**Other adverse effects****General regulation**

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

**SECTION 13: Disposal considerations****Waste treatment methods****Waste code No.**

15 01 10\*

**Name of waste**

packaging containing residues of or contaminated by dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.



---

**Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Dispose of according to the local waste regulations.

**General information**

For proper waste disposal a complete emptying of the tin is necessary.

---

**SECTION 14: Transport information****Land and inland navigation transport ADR/RID**

UN 1950 AEROSOLS, 2.1, (D), Classification code: 5F  
transport in "limited quantities" according to 3.4 ADR is possible

**Marine transport IMDG**

UN 1950 AEROSOLS, 2.1  
Transport as limited quantities according to 3.4 IMDG Code is possible.

**Air transport ICAO/IATA-DGR**

UN 1950 Aerosols, flammable, 2.1

**Transport/further information**

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

**Special precautions for user**

No information available.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

---

**SECTION 15: Regulatory information****Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard****Remark**

Daten separat anfragen / Request data separately.

**Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

---

**SECTION 16: Other information****Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

**Further information**

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

**Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)**

R 10 Flammable.

R 11 Highly flammable.

R 12 Extremely flammable.

R 15 Contact with water liberates extremely flammable gases.

R 20/21 Harmful by inhalation and in contact with skin.

R 36 Irritating to eyes.

R 37 Irritating to respiratory system.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 66 Repeated exposure may cause skin dryness or cracking.

R 67 Vapours may cause drowsiness and dizziness.

EUH066 -?-

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

---



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 22.06.2012

revision 01.05.2012 (GB) Version 7.0

**Chrome Silver Spray (GB)**

---

H226	Flammable liquid and vapour.
H228	Flammable solid.
H261	In contact with water releases flammable gas.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.