



SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Name of product Anti-Seize ASA Assembly Spray (GB)
Code-Nr. 270000

Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)
Corrosion Protection and Lubricant

Details of the supplier of the safety data sheet

Manufacturer/distributor WEICON GmbH & Co. KG
Königsberger Straße 255, DE-48157 Münster
Postbox 84 60, DE-48045 Münster
Phone ++49(0)251 / 9322 - 0, Fax ++49(0)251 / 9322-244
E-Mail : info@weicon.de
Internet : www.weicon.de

Advice Abteilung Angebote, Verkauf, Export
Phone ++49(0)251 / 9322 - 0
E-mail (competent person):
info@weicon.de

Emergency telephone number

Emergency advice Giftnotruf Bonn: Bei Vergiftungen (in case of poisoning)
Phone ++49(0)228-19 240

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to 67/548/EEC or 1999/45/EC

F+; R12
N; R51/53
R67

R-phrases

12 Extremely flammable.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

Label elements

Labelling according to 67/548/EEC or 1999/45/EC

Remarks for labelling

The product is classified and labelled in accordance with EC directives.

F+ Extremely flammable
N Dangerous for the environment

R-phrases

12 Extremely flammable.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

S-phrases

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
35 This material and its container must be disposed of in a safe way.



Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed

22.06.2012

revision

01.05.2012 (GB) Version 7.0

Anti-Seize ASA Assembly Spray (GB)

- 36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
51 Use only in well-ventilated areas.
59 Refer to manufacturer/supplier for information on recovery/recycling.
61 Avoid release to the environment. Refer to special instructions/safety data sheets.

Special rules for supplemental label elements for certain mixtures

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

Without sufficient ventilation the formation of explosive vapour/air mixtures cannot be excluded. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Other hazards

Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

SECTION 3: Composition/ information on ingredients

Mixtures

Hazardous ingredients

CAS No	EC No	Name	[% weight]	Classification according to 67/548/EEC
1305-62-0	215-137-3	calcium hydroxide	< 2,2	Xi, R38-41
61641-74-5		propane/butane-mixture	40-50	F+, R12
64742-49-0	265-151-9	Naphtha (petroleum) hydrotreated , free of aromatics (note P: < 0,1% benzene)	< 17	F11; Xn R 65; Xi R38; R67; N R51/53
1314-13-2	215-222-5	zinc oxide	< 1,1	N R50-53

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
1305-62-0	215-137-3	calcium hydroxide	< 2,2	Skin Irrit. 2, H315 / Eye Dam. 1, H318
61641-74-5		propane/butane-mixture	40-50	Flam. Gas 1, H220 / Press Gas, H280
64742-49-0	265-151-9	Naphtha (petroleum) hydrotreated , free of aromatics (note P: < 0,1% benzene)	< 17	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Skin Irrit. 2, H315 / STOT SE 3, H336 / Aquatic Chronic 2, H411
1314-13-2	215-222-5	zinc oxide	< 1,1	Aquatic Acute 1, H400 / Aquatic Chronic 1, H410

REACH

CAS No	Name	REACH registration number
64742-49-0	Naphtha (petroleum) hydrotreated , free of aromatics (note P: < 0,1% benzene)	01-2119475514-35-xxxx

Description

Lubrication spray based on solvents. Propellant: propane / butane.

SECTION 4: First aid measures

Description of first aid measures

General information

Remove contaminated soaked clothing immediately.

In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.



In case of ingestion

Do not induce vomiting.
Refer to medical treatment.

Most important symptoms and effects, both acute and delayed

Physician's information / possible symptoms

The following symptoms may occur:

Unconsciousness

Anaesthetic state

Headache

Confusion

Dizziness

Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

Foam

Dry powder

Carbon dioxide

Extinguishing media which must not be used for safety reasons

Full water jet

Special hazards arising from the substance or mixture

Fire gas of organic material has to be classed invariably as respiratory poison.

Advice for firefighters

Special protective equipment for fire-fighters

Use breathing apparatus with independent air supply.

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

Additional information

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing.

Keep away sources of ignition.

High risk of slipping due to leakage/spillage of product.

Environmental precautions

Do not discharge into the drains or bodies of water..

Methods and material for containment and cleaning up

Take up with absorbent material.

After taking up the material dispose according to regulation.

Reference to other sections

No information available.



SECTION 7: Handling and storage

Precautions for safe handling

Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking
Do not spray on a naked flame or any incandescent material.
Pressurized container.
The product is combustible.
Vapours can form an explosive mixture with air.
Avoid effect of heat.

Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep in closed original container.
Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

Advice on storage compatibility

Do not store with combustible materials.

Further information on storage conditions

Protect from heat and direct solar radiation.
Storage temperature may not exceed 50°C (=122°F).
Store container at cool and aired place.
Keep in a cool place.

Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours Short-term	1450 1810	600 750	EH40/2005

Exposure controls

Respiratory protection

If ventilation insufficient, wear respiratory protection.
Breathing apparatus

Hand protection

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm;480min; 60min.

Eye protection

safety goggles

Skin protection

protective clothing

General protective measures

Do not inhale gases.
Do not inhale aerosols

Hygiene measures

At work do not eat, drink and smoke.
Wash hands before breaks and after work.



SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Form	Colour	Odour
aerosol	grey	solvent-like

Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
Ignition temperature	> 250 °C				
Lower explosion limit	0,6 Vol-%				
Vapour pressure	3,5 bar	20 °C			
Density	0,72 g/ml	20 °C			
Solubility in water					insoluble

Explosive properties

The product is considered non-explosive ; nevertheless explosive vapour/air mixtures can be generated .

Other information

No information available.

SECTION 10: Stability and reactivity

Reactivity

No information available.

Chemical stability

No information available.

Possibility of hazardous reactions

No information available.

Conditions to avoid

Keep away from heat.
Formation of explosive gas/air mixtures.

Incompatible materials

Materials to avoid
Reactions with acids, alkalies and oxidising agents.

Hazardous decomposition products

Carbon monoxide and carbon dioxide.

Thermal decomposition

Remark No decomposition if used as directed.

SECTION 11: Toxicological information

Information on toxicological effects

Experiences made from practice

Inhalation causes narcotic effect/intoxication.

Additional information

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

Labelling in compliance with the assessment procedure specified in the EC guidelines 1999/45/EC.



SECTION 12: Ecological information

Toxicity

No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

No information available.

Mobility in soil

No information available.

Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

Other adverse effects

General regulation

Do not allow uncontrolled leakage of product into the environment.
Product is not allowed to be discharged into aquatic environment.

SECTION 13: Disposal considerations

Waste treatment methods

Waste code No.

15 01 10*

Name of waste

packaging containing residues of or contaminated by dangerous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 91/689/EEC on hazardous waste.

Recommendations for the product

Remove in accordance with local official regulations.

Recommendations for packaging

Dispose of according to the local waste regulations.

General information

For proper waste disposal a complete emptying of the tin is necessary.

SECTION 14: Transport information

Land and inland navigation transport ADR/RID

UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS, Classification code: 5F
transport in "limited quantities" according to 3.4 ADR is possible

Marine transport IMDG

UN 1950 AEROSOLS (ZINC OXIDE, NAPHTHA (PETROLEUM)), 2.1

MARINE POLLUTANT: Yes

Air transport ICAO/IATA-DGR

UN 1950 Aerosols, flammable, 2.1

ENVIRONMENTALLY HAZARDOUS: Yes

Transport/further information

24h EMERGENCY CONTACT (TRANSPORT) +49(0)178 433 7434 (Consultank Lutz Harder GmbH)

Special precautions for user

No information available.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable



SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC standard

Remark

Daten separat anfragen / Request data separately.

Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

Further information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Danish MAL code: 2-1

Wording of the R/H-phrases specified in chapter 3 (not the classification of the mixture!)

R 11 Highly flammable.

R 12 Extremely flammable.

R 38 Irritating to skin.

R 41 Risk of serious damage to eyes.

R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 65 Harmful: may cause lung damage if swallowed.

R 67 Vapours may cause drowsiness and dizziness.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.